



US011866125B2

(12) **United States Patent**
Reimers et al.

(10) **Patent No.:** **US 11,866,125 B2**

(45) **Date of Patent:** ***Jan. 9, 2024**

- (54) **PEDAL POWERED RIDING BAG TRANSPORT CART/CYCLE**
- (71) Applicant: **Eric W. Reimers**, Missoula, MT (US)
- (72) Inventors: **Eric W. Reimers**, Missoula, MT (US); **Michael J. Deden**, Missoula, MT (US); **Dale H. Truett**, Missoula, MT (US)
- (73) Assignee: **Eric Reimers**, Missoula, MT (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

- (52) **U.S. Cl.**
CPC **B62M 6/45** (2013.01); **B62J 1/08** (2013.01); **B62J 11/05** (2020.02); **B62K 11/02** (2013.01); **B62K 11/14** (2013.01); **B62M 6/70** (2013.01)

- (58) **Field of Classification Search**
CPC ... **B62M 6/45**; **B62M 6/70**; **B62M 6/65**; **B62J 1/08**; **B62J 11/05**; **B62K 11/02**; **B62K 11/14**; **B62K 15/00**; **B62K 21/12**
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
2,908,510 A * 10/1959 Lossau F02B 61/02 180/219
3,247,923 A 4/1966 Cornell
3,605,929 A 9/1971 Rolland
3,648,795 A 3/1972 Moulton
3,777,836 A 12/1973 Riza
3,979,136 A 9/1976 Lassiere
4,874,055 A 10/1989 Beer
5,265,695 A 11/1993 Piazza
5,277,267 A 1/1994 Tiffany
5,328,193 A 7/1994 Shiew
5,697,467 A 12/1997 Gojack
5,899,284 A 5/1999 Reimers

(Continued)

Primary Examiner — Kevin Hurley
Assistant Examiner — Marlon A Arce
(74) *Attorney, Agent, or Firm* — Dawsey Co., LPA;
David J. Dawsey

- (21) Appl. No.: **17/582,076**
- (22) Filed: **Jan. 24, 2022**
- (65) **Prior Publication Data**
US 2022/0144379 A1 May 12, 2022


Related U.S. Application Data

- (63) Continuation of application No. 16/423,025, filed on May 26, 2019, now Pat. No. 11,260,935.
- (60) Provisional application No. 62/677,332, filed on May 29, 2018, provisional application No. 62/677,315, filed on May 29, 2018.

- (51) **Int. Cl.**
B62M 6/45 (2010.01)
B62K 11/02 (2006.01)
B62M 6/70 (2010.01)
B62J 11/05 (2020.01)
B62J 1/08 (2006.01)
B62K 11/14 (2006.01)

- (57) **ABSTRACT**
A pedal powered bag transport cart/cycle is a personal riding cart/cycle adapted to transport a rider and a bag. The cart/cycle is generally symmetrical about a longitudinal plane and includes a frame with a seat, a front wheel and steering components, a rear wheel, an inclined bag support, a pedal subassembly, and in some embodiments a motor assist subassembly and controls.

20 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,139,032	A	10/2000	Hartman	
6,659,208	B2	12/2003	Gaffney	
7,086,491	B2	8/2006	Matte	
7,537,076	B2	5/2009	Falkiner	
7,631,715	B2	12/2009	Falkiner	
7,690,390	B2	4/2010	Hopkins	
8,091,749	B2	1/2012	Stautzenberger	
8,308,178	B2	11/2012	Hoerdum	
8,365,850	B2	2/2013	Gal	
8,490,732	B2	7/2013	Sugimoto	
D745,843	S	12/2015	Wuttig	
9,199,147	B2	12/2015	Azizi	
9,339,431	B2*	5/2016	Menard	B62K 11/007
9,550,540	B1	1/2017	Wang	
10,016,666	B2	7/2018	Reimers	
10,179,624	B1	1/2019	ODonnell	
10,189,529	B1	1/2019	Wang	
11,260,935	B2	3/2022	Reime	
11,358,042	B2	6/2022	Reimers	
2008/0023236	A1	1/2008	Falkiner	
2010/0206652	A1	8/2010	Kielland	
2016/0052464	A1	2/2016	Wadey	
2017/0254137	A1	9/2017	Peck	
2017/0327084	A1	11/2017	Park	
2018/0022411	A1	1/2018	Kistemaker	
2018/0056152	A1	3/2018	Reimers	

* cited by examiner




FIG. 2




FIG. 3




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

PEDAL POWERED RIDING BAG TRANSPORT CART/CYCLE

This application is a continuation of U.S. nonprovisional application Ser. No. 16/423,025, filed on May 26, 2019, which claims the benefit of U.S. provisional applications No. 62/677,332 and 62/677,315 by the same inventors, filed 29 May 2018.

TECHNICAL FIELD

The present invention relates generally to accessories for golfers and particularly to personal power-assisted golf bag carts and methods for transporting golf bags and the golfer.

BACKGROUND ART

Although the purists in the golf community insist that the only way to properly play golf is to carry the golf bag, either personally or through the use of a caddy, many golfers prefer to use carts to transport the golf bags and associated equipment. While riding carts are required by many courses, a great number of players desire to gain at least some of the exercise benefits of more compact and efficient means of transporting themselves and their equipment during the round while avoiding the often higher costs of renting a multiplayer cart from the course. For this reason walking carts are popular, but a riding personal cart would be even better for those who wish to limit their exertions.

For many years pull carts, usually two-wheeled, were the norm. However, powered options, such as electric bag carts are fairly popular and gyroscopic two wheeled units with room for a rider and bag have been introduced.

Nonetheless, demand continues for more compact, more stable, more convenient, and lighter golf bag carts, particularly personal riding powered carts.

DISCLOSURE OF INVENTION

Accordingly, it is an object of the present invention to provide a pedal-powered, with motor assist, riding golf bag cycle for transporting a golf bag and rider in a highly stable manner.

Another object of the invention is to provide a riding personal golf cart/cycle which does not cause meaningful damage to fairways, rough, and other "through the green" areas of golf courses.

A further object of the present invention is to provide a riding cart system with convenient support of the golf bag between the legs of the rider.

Yet another object of the invention is to provide a riding powered cart which has a minimal footprint.

Another object of the invention is to provide a riding pedal-powered golf cart which is steerable by the rider and has sufficient power assist available to negotiate typical golf course terrain.

A further object of the present invention is to provide a single passenger riding golf bag cart which partially collapses to a storage mode for transport of storage.

Briefly, one preferred embodiment of the present invention is a personal riding golf cart/cycle adapted to transport a rider and a golf bag. The cart/cycle has the general shape of a two wheeled cycle. The cart/cycle is generally symmetrical about a longitudinal plane and includes a plurality of compatible subassemblies, each providing important functions to the whole. The subassemblies (each also designated as an "sba") include: a cycle frame subassembly; a

personal support subassembly; a front wheel/steering sub-assembly; a rear wheel subassembly; a bag support subassembly; a pedal subassembly, a motor-assist subassembly and a control subassembly. The user rides, steers, and controls the speed from a height-adjustable seat above approximately the front of the rear wheel and above the pedals and the golf bag. The golf bag and its contents golf bag are supported at an angle between the golfer's legs, which extend downward to pedals on either side of the frame. An electrical power-assist motor situated in the rear wheel hub is powered by a battery mounted on the frame and is controlled by control elements mounted on the steering unit. Portions of the personal, bag support, and steering subassemblies are collapsible for convenient transport and storage.

An advantage of the present invention is that it provides a simple, relatively lightweight, and comfortable single user powered riding golf cart which functions like a pedal-powered bicycle in many conditions but has a motor assist for climbing hills and negotiating difficult terrain.

Another advantage of the invention is that it is bilaterally symmetrical and relatively thin such that multiple units may be parked in a smaller space than conventional riding carts.

A further advantage of the invention is that a single passenger cart significantly improves the speed of playing a round, since it is not necessary to deal with two balls in play in widespread separations.

Yet another advantage of the present invention is that the cycle structure provides a familiar and comfortable means of transport for the golfer and equipment around the golf course.

Still another advantage of the present invention is that its wide tires minimize potential damage to turf and thus may be considered by many courses to be usable on the fairways and rough (grass covered portions) of the course, rather than restricted to cart paths, thus drastically aiding the comfort of the golfer and reducing the time taken to play a round of golf.

Another advantage of the present invention is that embodiments having partially collapsible aspects make it convenient for transport between home and also at the golf course and locations, rather than exclusively for storage at the course, although the preferred embodiment is adapted to transport on common bike-carriers.

A still further advantage of the present riding golf bag cart/cycle invention is that no straps or similar restraints are usually necessary to keep the golf bag in place and provide easy access to the clubs during use, although such straps or similar restraints may be provided for some embodiments.

Yet another advantage of the present invention is that the open frame of the bag support subassembly permits easy access to the pockets of the golf bag, so that the golfer may store and retrieve golf balls and accessories.

Another advantage of the present invention is that it provides the "feel" and locational convenience of a walking round, with significantly less stress or wear and tear on the golfer's body.

Still another advantage of the present invention is that it may be operated using only pedal power, using only motor power, or both together, depending on the terrain and the desires of the rider.

An additional advantage of the present invention is that the limited power of the motor component facilitates the use of the cart/cycle on streets so that the rider can use it for transport other than on a golf course.

These and other objects and advantages of the present invention will become clear to those skilled in the art in view

3

of the description of the best presently known mode of carrying out the invention and the industrial applicability of the preferred embodiment as described herein and as illustrated in the several figures of the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The purposes and advantages of the present invention will be apparent from the following detailed description in conjunction with the appended

FIG. 1 is a front right elevational view of the riding cycle golf bag cart of the present invention, illustrating (in phantom) a golf bag carried thereon;

FIG. 2 is a left elevational view of the riding cycle golf bag cart of the present invention;

FIG. 3 is a right side elevational view of the present invention;

FIG. 4 a rear right side perspective view of the presently preferred embodiment of the invention;

FIG. 5 is a front elevational view of the invention;

FIG. 6 is a rear elevational view of the rideable golf bag cart/cycle of the present invention, showing a rider in phantom;

FIG. 7 is a top view of the preferred embodiment;

FIG. 8 is a bottom view; and

FIG. 9 is a front view, similar to FIG. 5, showing the collapsed mode of the invention.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention is personal riding golf bag cart in the form of a riding cycle used to transport the user along with golf bags loaded with golf clubs and accessories. The pedal-powered riding golf bag cart/cycle is referred to by the general reference character 10, generally referred to as "riding cart 10", in the description. The riding cart 10 is generally symmetrical about a vertical (in normal operation) longitudinal plane 11. The riding cart 10 may be used with various golf bags 12 and may exist in multiple embodiments. The pedal-power is directly provided by the golfer/rider 13 (shown in phantom in FIG. 6) and is adapted to be assisted by a motor, as discussed below.

In one preferred embodiment of the invention illustrated in FIGS. 1 and 4, the riding cart 10 is shown in a perspective view as appropriate for transporting the typical golf bag 12 as well as a golfer/rider 13 (not shown). Although oversized "power-cart" golf bags are generally too large in diameter for comfortable riding between the rider's legs (and may interfere with pedaling and moving components) most conventional golf carry bags and slim-line cart bags are workable and comfortable.

The riding cart 10 may be thought of as having various principal assemblies or subassemblies (each sometimes referred to in shorthand as a "sba" herein) which operate together in order to function as an easy to use method of transporting a golf bag on the rolling surfaces of a golf course and in other locations such as parking lots and storage facilities. The primary subassemblies include: a frame sub-assembly (sba) 14; a personal support sba 16; a front wheel and steering sba 18, a rear wheel sba 20, a bag support sba 22, a pedal sba 24, a motor-assist sba 26, and a motive control sba 28. It is understood that some components of the invention interface with others and may be considered to be a part of more than one of the subassemblies. As discussed further below, some of the sbas in alternate embodiments may have structures and features which allow them to be

4

physically manipulated to create a collapsed/storage mode 30 having a lower and shorter aspect for transport and storage.

As best seen in FIGS. 1-4 and 8, the frame subassembly 14 includes a convoluted frame tube structure 32, aligned within the vertical longitudinal plane 11, which mates together with a steering bracket 34 (part of the front wheel/steering sba 18) at the front of the frame 14. The frame tube 32 extends rearward along the longitudinal plane 11 from the steering bracket 34. A front angle tube 36 is affixed to the stationary steering bracket 34 and is angled downward to intersect at an approximately right angle to bond with a lower extent of a seat tube 38. A pedal support tunnel 40 extends laterally through the front angle tube 36 forward of the seat tube 38. The seat tube 38 extends below the intersection with the front angle tube 36 to support a horizontally arrayed undercarriage 42. The frame sba 14 also includes a rocker arm fork 46 pivotally extending from the angle tube 36. A brace fork 48 extends rearward and downward from the upper portion of the seat tube 38 to mate with the rocker arm 46. A kickstand 50 pivotally depends from lower portion of the angle tube 36, and may be engaged to maintain the bag cart/cycle 10 in a generally vertical orientation when unoccupied by the rider 13 and then manually disengaged when motion is desired.

The personal support sba 16 is an adjunct to the cycle frame sba 14. The personal support sba 16 includes a seat 50 having a cushion 52. The seat 50 is mounted on and above the seat tube 38 with a height adjustable mounting bracket 54 so that the rider 13 is comfortable with operating the pedal sba 24. The seat 50 provides support for the golfer/rider 13 during use. Typically, the seat 50 may be mounted by the rider 13 either from the rear or, if feasible, from either side.

The front wheel/steering subassembly 18 includes a front fork 58 pivotally mounted to depend from the steering bracket 34. The front fork 58 includes a fork bracket 60 pivotally connected to the steering bracket 34 and supports a pair of opposed fork arms 62 depending therefrom, each optionally including a shock absorber 64. The fork arms 62 support a front wheel 66 on a front axle 68 extending between the lower extent of the opposing fork arms 64. The front wheel 66 has a substantial diameter and supports a front tire 70 having a moderately wide tread for traction while being pneumatic and relatively soft so as to avoid damaging the turf in use. A front fender 71 may be mounted between the arms of the front fork 58 above the front tire 70 to minimize splashing or debris from impacting the rider 13 or the golf bag 12.

In the preferred embodiment 10 the upper portion of the front wheel/steering sba 22 includes a set of handlebars 72 pivotally attached to the fork bracket 60 by pivot tubes 74 on either side. Each handlebar 72 is bent outwards to form a curved tube 76 pivotally extending above the respective pivot tube 74 in order to facilitate steering and turning without impacting the golf bag 12 which extends therebetween. The curved tube 76 extends upward to handle grips 78 for comfortable hand positioning and steering. The pivotal attachment of the handlebars 72 to the fork bracket 60 allows the handlebars 72 to pivot downward around the front 70 tire in the compact storage mode 30 (see FIG. 9). The curved tube 76 may also be rotated on the pivot tube 74 such that the handle grips 78 are aligned to be generally parallel with the front tire 70, thus minimizing net width in the collapsed storage mode 30.

The rear wheel subassembly 24 includes the previously described rocker arm fork 46 and brace fork 48 which

together function as a rear fork **80**. The rear fork **80** supports a rear wheel **82** having a hub **83** surrounding a rear axle **84**. The rear wheel **82** is generally dimensionally the same as the front wheel **66** and supports a rear tire **86**. The rear tire **88** is wide similarly to the front tire **66** to provide good driving traction while minimizing impact on the turf of the course. The rear tire **86** may be inflatable or solid. A fender **88** may be attached to the rear fork **80** or to the seat fork segment **44** to extend over the upper portion of the rear tire **86**.

The bag support **sba 22** is adapted to hold the golf bag **12** in place on the cart/cycle **10**. The golf bag **12** is supported at about a forty-five to sixty five degree vertical angle, twenty five to forty five degrees to the horizontal, (with the club heads extending forward through the handlebars **72** and above the front wheel **66**). The base of the golf bag **12** rests upon a bag bottom cradle **90** and may abut against the seat tube **38**. The bag bottom cradle **90** is shaped to have wings **91** which extend upward and outward to hold the bag bottom up and laterally in place.

An upper bag cradle **92** is mounted on the steering bracket **34** to laterally cradle the upper part of the golf bag **12** and prevent the golf bag **12** and clubs from interfering with the handle bars **72**. It is noted that the upper bag cradle **92** is stationary on the stationary steering bracket **34** and does not rotate with the handlebars **72**. This arrangement maintains the golf bag **12** in position to be always centered on the longitudinal plane **11** even when the cart/cycle **10** is being steered around curves (the handlebars **72** being spread wide enough that the curved tubes **76** do not contact the golf bag **12** in any but the most extreme turns).

The pedal subassembly **24** facilitates operating the cart/cycle **10** either by itself or in combination with the motor assist **sba 26**. The components of pedal subassembly are all situated in the vicinity of the pedal support tunnel **42** discussed above. A pair of vertically opposed pedal arms **94**, each including a rotatable pedal **96**, are rigidly connected by a pedal axle **98** passing through the pedal support tunnel **40**, cause a sprocket **100** to rotate when the rider **13** rotates the pedal **sba 24** (in a similar manner to that of operating a conventional bicycle). When the cart/cycle **10** is operating in a pedal-only mode, it operates in the same manner as a conventional bicycle.

The sprocket **100** in the preferred embodiment is a toothed disk **102** which drives a similar (if smaller) rear disk **104**, connected to the rear wheel axle **84**, by virtue of a drive chain **106**. Other drive concepts may also work, such as a belt drive, but the sprocket and chain mechanism is more reliable for pedal power. It is noted that the pedal power works only to propel the cart/cycle **10** forward and is not usable for reverse motion.

The motor assist **sba 26** provides the power to move the cart/cycle **10** and the golfer **13** around the course, either providing sole power of operating to assist the pedal **sba 24**. The presently preferred embodiment **10** is a rear wheel drive system with an electrical motor **108** and a rechargeable battery **110**. The electrical motor **108** in the present embodiment is a disc motor situated in the hub **83**. Other motive systems may drive the rear wheel by any of a variety of mechanisms, including a chain drive, or a belt drive. The battery **110** may be mounted at various locations on the cycle frame **14**, with the preferred version being a battery cradle **112** nested within the undercarriage **42**.

The electrical motor **108** is intentionally limited in power in order to be "street legal" in most jurisdictions. This allows the cart/cycle **10** to be ridden to and from the course or on other errands unrelated to golf. Even in motor-assist or motor only modes.

In a motor assist mode, the motor **108** provides additional motive power to the rear wheel **82** to assist the force being provided by the rider **13** using the pedals **96**. In this mode the electrical drive provides additional rotational energy which helps the rider **13** in situations where pedaling is difficult, such as when climbing hills or working in difficult terrain. In this mode the motor **108** does not supplant the pedal drive **sba 24** but merely helps out.

The cart/cycle **10** can also be operated solely on motor power when the rider **13** wishes to rest. To facilitate this, a decoupler **114** is provided to decouple the pedal **sba 24** from the rear axle **84** such that the pedals **96** are not forced to rotate during a motor-alone mode operation. This mode is ordinarily used on relatively flat terrain in the preferred embodiment since it is not intended, for overall weight and cost considerations, that the preferred motor **108** is powerful enough to handle steep inclines with a normal or heavy rider **13** aboard.

The operational mode and speed of the motor **108** will typically be regulated by the golfer **13** by a control unit **116** usually mounted on one of the handlebars **72**, normally adjacent to or part of the handle grips **76**. The control unit **116** has settings which allow the motor **108** to be set to off **118**, motor-assist **120**, and motor only **122** (which also engages the decoupler **114**). A throttle control **124** allows the rider **13** to select the speed/rotational force in motor-assist and motor only modes. An optional speedometer **126** may also be provided to allow the rider to know the velocity of travel.

A brake actuator **128**, also typically situated near a handle grip **74**, will control a brake **130** applied to one or both of the front wheel **66** and/or the rear wheel **82**. The front brake **132** will typically be a conventional friction brake while a rear brake **134** may be a motor brake, a disc brake, or a friction brake.

The preferred embodiment **10** is primarily constructed of cast or extruded anodized aluminum for light weight and durability. The wheels **66** and **82** are pneumatic tires with cushioned traction surfaces and may either be provided with solid hubs or spoke hubs (although the rear wheel will have a hub for containing the electric motor **108**).

In one embodiment (see FIG. 9) the cart/cycle **10** may be converted to the collapsed mode **30** for storage or transport. In this instance, each handlebar **72** is rotated downward upon the fork bracket **60** to extend to either side of the front wheel **66**, thus reducing the overall height of the assembly. It is envisioned that other modification intended to reduce the "footprint" of the cart/cycle **10** may also be feasible, but generally the entire unit is compact enough for most storage situations and is adapted to fit on a conventional bicycle vehicle rack for transport.

Many modifications to the above embodiment may be made without altering the nature of the invention. The dimensions and shapes of the components and the construction materials may be modified for particular circumstances or types of bags to be carried.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not as limitations.

INDUSTRIAL APPLICABILITY

The rideable pedal/motor golf bag cart/cycle **10** of the present invention is intended for use primarily by golfers who desire physical exercise along with maximum convenience and safety while transporting a golf bag **12** and a rider **13** during a round of golf. The cart/cycle **10** is relatively

lightweight and is suitable for transport on ordinary cycle racks. Like any cycle having two wheels, the cart/cycle **10** does not require balancing by the rider **13** when in motion and tip-prevention by the kickstand **50** when not attended. The general symmetry of the cart/cycle **10** about the longitudinal plane **11** substantially aids in keeping the unit balance. The cart/cycle **10** also requires no straps or other fasteners to retain and support the golf bag, thus minimizing the amount of loose or dangling components and reducing effort.

For typical use, the riding golf bag cart/cycle **10** will be in a rest position (collapsed mode **30**) with the motor **108** off and the kickstand **50** activated. The rider **13** (or a worker) will then slide the golf bag **12** bottom first to rest against and on the restraints defined by the bag bottom cradle **90**, the pair of bag bottom wings **91**, and the seat tube **38**. The upper portion of the golf bag **12** will rest against the upper bag cradle **92** which will provide vertical support and at least some lateral restraint. The golf bag **12** will be maintained to be centered on the longitudinal plane **11** (balance-centered) to rest at about an optimal thirty degree angle from horizontal such that golf clubs will extend forward and upward over the front wheel **66** for easy access. The rider **13** will adjust the seat **52** on the mounting bracket **56** to the proper height, and mount the cart/cycle **10** to sit upon the seat **52**. The legs of the rider **13** will straddle the bottom extent of the golf bag **12** and extend downward to the pedals **96**.

In order to move forward, the seated rider **13** may set the control unit **116** via the off control **118** and manually propel the cart/cycle **10** in pedal mode by using the pedals **96**. In motor assist mode the motor assist control **120** is utilized to activate the control unit **116** to start the electric motor **108** while continuing the pedal operation and using the throttle control **124** to select the amount of assisted power to be provided to the force manually provided by the rider **13**. In motor-only mode the motor-only control **122** is utilized to activate the motor and activate the decoupler **114** and the throttle control **124** is set to control the speed of rotation of the rear wheel **86** to drive the cart/cycle **10** forward at the desired speed. The brake actuators **128** will be activated to use the brake(s) **130** to slow or stop the travel when needed (such as on downslopes or on reaching the destination location). The rider **13** will then dismount, activate the kickstand **50** (or lean the cycle **10** against an object such as a tree or bench), play the next stroke(s) and repeat the process to proceed to the next location.

When the round is over, the golfer simply: dismounts; activates the kickstand **60** (or parks in a designated spot which prevents tipping); and removes the golf bag **12** from the cart **10**, rotates the handlebars **72** to the compact mode **30** if desired, and either stores or transports the cart/cycle **10** to a storage location.

The extreme convenience, ease of operation, relative compactness, and light weight of the inventive cart/cycle **10** make it a joy to own and use and a desirable accessory for any golfer who wishes to traverse the course without carrying the weight of the bag. The wide and relatively soft front tire **70** and rear tire **86** minimize disruption of the turf on the course and facilitate access to the areas of the course upon which powered units are permitted.

For the above, and other, reasons, it is expected that the collapsible riding golf bag cart/cycle **10** of the present invention will have widespread industrial applicability. Therefore, it is expected that the commercial utility of the present invention will be extensive and long lasting.

We claim:

1. A pedal powered motor-assisted rideable bag transport cart/cycle, comprising:

a cycle frame supporting a front wheel, a rear wheel aligned with the front wheel, and a seat;

a steering subassembly including a right handlebar and a left handlebar creating a handlebar void therebetween to receive a portion of a bag, wherein the right and left handlebars are rotatably coupled to the cycle frame and turn the front wheel;

a pedal subassembly on said cycle frame, including a drive chain for rotating the rear wheel;

an electric motor for providing a motor-assist to rotation of said rear wheel, said electric motor being controlled by a control subassembly; and

a bag support subassembly on said cycle frame adapted to support and position the bag so that (a) a portion of the bag is located within the handlebar void between the right handlebar and the left handlebar, which rotate relative to the stationary bag, and (b) a portion of the handlebar void and a portion of the bag extend over a portion of the front wheel.

2. The bag transport cart/cycle of claim 1, wherein the bag support subassembly includes a bag top support that is stationary with respect to the handlebars, with a portion of the bag top support located above an elevation of a top of the front wheel.

3. The bag transport cart/cycle of claim 2, wherein a portion of the bag top support is located vertically above a portion of the front wheel.

4. The bag transport cart/cycle of claim 2, wherein the bag support subassembly includes a bottom bag support located below an elevation of the seat.

5. The bag transport cart/cycle of claim 2, wherein the right and left handlebars are individually coupled to a fork bracket.

6. The bag transport cart/cycle of claim 5, wherein the right and left handlebars are pivotally coupled to the fork bracket such that they may be rotated downward about said front wheel to a collapsed position.

7. The bag transport cart/cycle of claim 6, wherein the right and left handlebars rotate forward and away from the seat and cycle frame to the collapsed position.

8. The bag transport cart/cycle of claim 5, wherein a pair of fork arms separately attach to the fork bracket and the front wheel.

9. The bag transport cart/cycle of claim 2, wherein at least a portion of the bag top support is located forward of the handlebars.

10. A pedal powered bag transport cart/cycle comprising; a cycle frame having a front wheel, a rear wheel aligned with the front wheel, a seat, and handlebars for steering including a right handlebar and a left handlebar creating a handlebar void therebetween to receive a portion of a bag, wherein the right and left handlebars are rotatably coupled to the cycle frame;

a lower bag support and an upper bag support mounted on said frame to support and position the bag so that (a) a portion of the bag is located within the handlebar void between the right handlebar and the left handlebar, which rotate relative to the stationary bag, and (b) a portion of the handlebar void and a portion of the bag extend over a portion of the front wheel; and

a pedal subassembly including a pair of opposing pedals operatively joined to the rear wheel to move the cart/cycle forward.

11. The bag transport cart/cycle of claim 10, further including a motor for driving said rear wheel, wherein the pedal subassembly and the motor may be operated individually or in combination.

12. The bag transport cart/cycle of claim 10, wherein the right and left handlebars are individually coupled to a fork bracket.

13. The bag transport cart/cycle of claim 10, wherein a portion of the upper bag support is located vertically above a portion of the front wheel and the lower bag support is below an elevation of the seat.

14. The bag transport cart/cycle of claim 10, wherein at least a portion of the upper bag support is located forward of the handlebars.

15. A bag transport cart/cycle for transporting a rider and a bag, comprising:

a cycle frame and having a front wheel and a rear wheel aligned with the front wheel, and a seat;

a lower bag support and an upper bag support, stationary with respect to the frame, for supporting the bag, with the lower bag support located at a lower support elevation and closer to the rear wheel than the front wheel, and the upper bag support is located at an upper support elevation and closer to the front wheel than the rear wheel, with the upper support elevation greater than the lower support elevation;

a right handlebar and a left handlebar creating a handlebar void therebetween to receive a portion of the bag such that (a) a portion of the bag is within the handlebar void

between the right handlebar and the left handlebar, which rotate relative to the stationary bag, and (b) a portion of the handlebar void and a portion of the bag extend over a portion of the front wheel;

a highest point on the upper bag support is at an elevation above a highest point on the front wheel and below a highest point on the right and left handlebars, and a portion of the upper bag support is vertically above a portion of the front wheel.

16. The bag transport cart/cycle of claim 15, further including a pedal subassembly including a pair of opposing pedals operatively joined to the rear wheel to move the cart/cycle forward.

17. The bag transport cart/cycle of claim 15, further including a motor for driving said rear wheel.

18. The bag transport cart/cycle of claim 17, wherein a pair of fork arms separately attach to a fork bracket and the front wheel.

19. The bag transport cart/cycle of claim 18, wherein the right and left handlebars are individually coupled to the fork bracket.

20. The bag transport cart/cycle of claim 19, wherein at least a portion of the upper bag support is located forward of the handlebars.

* * * * *